

Rockford Fosgate P300-12 Teardown

Rockford Fosgate P300-12 12" 300W powered subwoofer

Written By: bassblaster505





• Essential Electronics Toolkit (1)

Step 1 — Rockford Fosgate P300-12 Teardown



Front view

Step 2









Remove the 8 coarse thread wood screws and gently pry the plate out







 Carefully remove the 3 knobs and the 1 screw between the 2 10A fuses. then the plastic face should pop off








- Crossover / Gain
- Power Supply and output FET's
- Power Supply Transformer
- Output Filters
- The 2 boards are held together by 4 screws on the edges of the PCB, gently pull them apart, they will only be held together by pin headers. Here you can see the 2 output filters and the power supply step up transformer
- The board with the FEMALE pin headers is the front board with the plugs on it. the crossover network consists of JRC 4850's



- There are 4 of these "GA7E1S"
 FET's that i cant find any info on. i
 would assume by looking at the
 boards that 2 are the power supply
 and the other 2 are the outputs
- There are NO heatsinks anywhere in this unit which i find amazing, but the FETS most likely use the massive copper planes on the board as the heatsink

Step 6



More jelly bean logic around the board





 The custom 12" driver. it appears to be a DVC driver, but it just a SVC with 2 pairs of leads going to it