



Garmin Fenix 3 Wrist Strap Replacement

Replace the torn or damaged wrist strap for your smartwatch.

Written By: Adam Estabrook



INTRODUCTION

This replacement will require use of both hands and unusual hand placement. Pay close attention to the images to ensure success in replacing this part.



TOOLS:

- [T6 Torx Screwdriver](#) (2)

*Due to the nature of the wrist strap's fastenings,
two screwdrivers are required.*

Step 1 — Wrist Strap



- Identify the screws near the bases of two wrist straps.

Step 2



- Hold one screwdriver firmly in one hand, as demonstrated in the image.

Step 3



- Secure the watch in the same hand, positioning the screwdriver over the screw.

Step 4



- Once the watch is secure, insert the screwdriver into the screw, and hold firmly.

Step 5



- With the watch and the first screwdriver secure, insert the second screwdriver into the opposite screw.
- Holding the first screwdriver firmly, unscrew using the second screwdriver.

Step 6



- Remove the bar from the wrist strap to release.
- ⓘ Depending on which side the bar is inserted, you may end up loosening the screw instead of the bar. Keep this in mind to avoid losing your screws.

Step 7



- Repeat this process for the other side, adjusting the position of the watch accordingly.

To reassemble your device, follow these instructions in reverse order.