



# Beats Solo 3 Battery Replacement

This is a battery replacement guide for Beats...

Written By: McKenzie Hosey



# INTRODUCTION

This is a battery replacement guide for Beats Solo3. The model number is A1796. This guide will show you how to correctly remove and replace the battery for your headphones. For this guide you will need a pry or opening tool and an optional pair of tweezers. The battery for the headphones is the UltraLast Lithium-Polymer battery. The battery powers the headphones. Symptoms which can result in a battery replacement can be found on our [troubleshooting page](#).

---

## TOOLS:

[iFixit Opening Tool](#) (1)  
[Tweezers](#) (1)

## PARTS:

[Beats Solo 2/3 Battery](#) (1)

---

### Step 1 — Battery



- Pry off the outside pane on the right side of the headphone with an opening tool.

## Step 2



- You should see your battery here. It will be square with yellow packaging.

⚠ Be sure not to pull on the wires that are connected to the outside panel. This may cause damage to your headphones.

## Step 3



- Grasp the battery's small bundled connector, and pull gently to remove.
- Carefully remove the top attachment from the headphones with tweezers or your fingers.

## Step 4



- Use an opening tool or a nylon spudger to carefully remove the battery. Make sure you pry upward.  
⚠ Do not bend or puncture the lithium-ion battery.
- Once that is removed, make sure you peel off the sticker where the battery is placed if it is stuck to the battery.
- If it is, then place it back where it belongs in the headphones.

---

To reassemble your device, follow these instructions in reverse order.