


# **HTC Evo 4G Rear Inner Frame Replacement**

Rear inner frame replacement.

Written By: Walter Galan



# **INTRODUCTION**

Remove the rear inner frame to gain access to the internals of the HTC Evo 4G.



# **TOOLS:**

- Spudger (1)
- T5 Torx Screwdriver (1)
- Tweezers (1)
- iFixit Opening Tools (1)

#### Step 1 — Rear Panel



- Gently insert an iPod opening tool between the rear panel and the inner rear frame near the headphone jack.
- Use your iPod opening tool to pry up the rear case around the perimeter of the Evo.

# Step 2



 Lift the rear panel off of the inner rear frame.

#### Step 3 — Battery






- Using the tip of your finger, lift the battery from the end closest to the camera.
- Remove the battery from the rear inner frame.

# Step 4 — MicroSD card



- Use the flat end of a spudger to pry up the red MicroSD retainer attached to the inner frame.
- The retainer will move about 1 mm and stop. Do not attempt to completely remove the MicroSD card retainer.

# Step 5



 Use a pair of tweezers to carefully pull the MicroSD card out of its slot in the inner rear frame.

# Step 6 — Rear Inner Frame



 Remove six T5 Torx screws securing the rear inner frame to the inner case.

#### Step 7



- Gently insert an iPod opening tool between the rear inner frame and its plastic surround near the Micro HDMI port.
- Carefully pry the top edge of the rear inner frame away from the front surround of the Evo.

#### Step 8





• Insert the iPod opening tool between the rear inner frame and its plastic surround and pry up at several points along the left edge of the Evo.

#### Step 9








- Continue the prying procedure, now focusing on detaching the plastic surround from the bottom of the Evo.
- Pry up the rear inner frame along the right edge using the method described in previous steps.
- Eventually work around the entire perimeter of the rear inner frame until it is lifted slightly from the inner case.

#### Step 10



 Remove the rear inner frame from the rest of the Evo.

To reassemble your device, follow these instructions in reverse order.

This document was generated on 2020-11-17 10:55:36 PM (MST).