



Samsung Captivate Rear Case Replacement

Cracked frame? Use this guide to repair your...

Written By: Christopher



INTRODUCTION

Cracked frame? Use this guide to repair your Captivate's rear case.

TOOLS:

Phillips #000 Screwdriver (1)

Spudger (1)

Step 1 — Battery



- Remove the back cover by pressing on the bottom section of the phone and sliding the bottom piece downward.
- Lift up the back cover.

Step 2



- Place your finger on the bottom of the battery and lift to remove.

Step 3



- Replace the old battery with the new one.

Step 4 — Rear Case




- Insert the spudger underneath the bottom section of the phone.
- Gently lift and push the spudger to slide the bottom section down to reveal two hidden screws.

Step 5



- Remove the six 4.5mm #000 Phillips screws.

Step 6



- Starting at a bottom corner, use the spudger to separate the rear case from the front display.
- Move the spudger towards the top on both sides. The plastic opening tool is easier to use for this step.

⚠ Be careful when detaching the top. Free each side, stopping short of the center of the cover. Apply backward pressure on both corners with a finger applying pressure on the center, and slide the whole back cover toward the bottom of the device. Note: forcing the cover can result in cracked plastic.

Step 7



- Separate the rear case from the phone.

To reassemble your device, follow these instructions in reverse order.

