




1986-1993 Volvo 240 Manual Transmission Replacement

Remove or replace the manual transmission in a Volvo 240

Written By: Phillip Takahashi



Step 1 — Manual Transmission




- Lift the bottom of the shift boot to expose the shifting socket.
- Use snap ring pliers to remove the circlip securing the shifter to its socket.

Step 2




- Remove the set screw securing the shifter yoke pin. This assembly can be located on the underside of the car, above the transmission and directly below the shift lever.
- Grab the head of the shifter yoke pin with your hands or pliers and pull it out.
 - ⓘ If the pin won't readily come free, try jiggling the shifter while you pull the pin.

Step 3



- Remove the shift lever by pulling it straight up.
- Remove the plastic bushing in the bottom of the shifter socket.


Step 4



- Remove the 6 nuts and bolts securing the drive shaft to the guibo and the back side of the transmission.
- ⓘ Only four nuts and bolts are visible and marked in the first picture. The others are hidden on the other side of the drive shaft.
- ★ Take note of how the bolts, washers and guibo are positioned. They are required to go back in the same way.




Step 5



 Support the drive shaft with a jack, jack stand, or other prop so it does not fall and get damaged or injure someone when the support is removed.

- Remove the 4 bolts securing the drive shaft support.
 - ⓘ Do not lose the washers on the 4 bolts or the spring and washer on the opposite side of the support.
- Slowly lower the drive shaft and separate it from the transmission.
- Remove the guibo and metal separator plate.
 - ⓘ The separator may not come out with drive line and will be in the transmission.

Step 6



- Remove the bolts securing the transmission to the engine and to the starter.
- ⚠ Support the transmission so it doesn't fall when the final support is removed.
 - Generally, a jack is recommended for this.
- Remove the four bolts securing the transmission support to the chassis.
- Lower the transmission out of the car.
 - In many instances, the transmission may not come free from the engine once the bolts are removed. If this is the case, a pry bar is recommended to help separate the two.

To reassemble your device, follow these instructions in reverse order.